

## TECHNICAL DATA SHEET



# SYNTHETIC 0W-10 RACING ONLY

**PRODUCT #10286, 10287, 10288,  
10289, 10290, 10371**

### TEST

### ASTM

### TYPICAL

<b>API Gravity</b>	<b>D-1298</b>	<b>36.1</b>
<b>Specific Gravity @ 60°F</b>	<b>D-1298</b>	<b>.8443</b>
<b>Density @ 60°F LBS/US Gal</b>	<b>D-1298</b>	<b>7.303</b>
<b>Viscosity @ 40°C, cSt</b>	<b>D-445</b>	<b>22</b>
<b>Viscosity @ 100°C, cSt</b>	<b>D-445</b>	<b>5</b>
<b>Viscosity Index</b>	<b>D-2270</b>	<b>162</b>
<b>Color</b>		<b>Amber</b>
<b>Flash Point, COC °F</b>	<b>D-92</b>	<b>317</b>

**Lucas Oil Products Synthetic 0W-10 Pro Stock Oil is a 100% Synthetic, ULTRA-light viscosity, RACING MOTOR OIL. Developed for high RPM naturally aspirated gasoline engines, it is excellent for gapless or extra light tension rings.**

**Provides maximum horsepower gains in Pro Stock, Pro Stock Bike and Competition Eliminator, while providing excellent protection and reducing friction at high RPM's.**

**An excellent qualifying oil for NASCAR, NHRA, IHRA or any race engine designed to run lighter viscosity motor oils.**

**Our exclusive Anti-Wear and Anti-Scuff Extreme Pressure additive package protects the valve train, bearings and cylinder walls.**

**Designed to run at operating temperatures up to 190°F, although it will provide protection up to 250°F.**

**Not intended for passenger car use.**